



# Material Safety Data Sheet

---

**Product Name: Self-Saturating Foam Tipped Swab (Snap-Swab)**

Product Number: K2-SPSB25, K2-SPSZ50, K2-SPSN1

General Use: Technical Cleaning

Product Description: Squeeze or Snap the handle end and the swab will self saturate.

## SECTION I

### Manufacturer's Name & Address:

KICTeam, Inc.  
P.O. Box 1120  
Auburn, ME 04211-1120  
Phone (207) 514-7299  
FAX: (207) 514-7033

Emergency Telephone: (800) 424-9300  
Telephone for information: (800) 255-3924  
Date Prepared: May, 2008

Complies with OSHA's Hazard Communication  
Standard 29 CFR 1910.1200

## SECTION II - Hazardous Ingredients/ Identity Information

Hazardous Components	CAS #	OSHA PEL.	ACGIH TLV	%
Isopropyl alcohol	67-63-0	500 ppm STEL		91%

This Product contains the following chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372: NONE

## SECTION III - Physical/Chemical Characteristics

Boiling Point: 180.07F

Percent Volatile: 91%

Evap. Rate: 2.88 (Butyl Acetate = 1)

Vapor Density (AIR=1) 2.07

Solubility in Water

Appearance and Odor



## **SECTION IV - Fire and Explosion Hazard Data**

Flash Point (Method Used): TCC 63F, 17 C (Tag Open Cup ASTM D 1310)

Flammable Limits:

Extinguishing Media: CO<sub>2</sub>, Foam, Dry Chemical

Unusual Fire Hazards: Vapors form from this product and may travel or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. Vapors from this material may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard.

## **SECTION V - Reactivity Data**

Stability: Stable

Hazardous Polymerization:

Conditions to Avoid: None known.

Incompatibility (Materials to avoid): Strong oxidizing agents, halogens, strong inorganic acids, aldehydes, and halogen compounds.

Hazardous Decomposition or Product:

## **SECTION VI - Health Hazard Data**

Primary Route(s) of Exposure: Swallowing, skin contact, inhalation and eye contact.

Acute Effects:

Swallowing: Slightly toxic. May cause abdominal discomfort, nausea, vomiting, diarrhea, loss of consciousness and drowsiness.

Inhalation: Vapor causes irritation of the respiratory tract, with coughing and chest discomfort.

Skin contact: May cause minor irritation with itching and possible slight local redness.



Prolonged or repeated contact may cause defatting and drying of the skin.

Eye contact: Causes irritation, experienced as stinging and discomfort or pain. Corneal injury may occur.

Chronic: No adverse effects anticipated from available information.

### **Emergency and First Aid Procedures:**

**SWALLOWING:** If patient is fully conscious, give two glasses of water. Induce vomiting and seek medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Wash skin with soap and water. If irritation persists or if contact has been prolonged, obtain medical attention.

**INHALATION:** Remove to fresh air. Give artificial respiration if not breathing. If breathing is difficult, oxygen may be given by qualified personnel. Obtain medical attention.

**EYES:** Immediately flush eyes with water and continue washing for several minutes. Obtain medical attention.

### **SECTIONS VII - Precautions for Safe Handling and Use**

**Steps to Be Taken in Case Material is Released or Spilled:** Extinguish and do not turn on any ignition source until the area is determined to be free from fire or explosion hazard. Wear suitable protective equipment. Avoid contact with eyes. Small spills can be flushed with large amounts of water; larger spills should be collected for disposal.

**Waste Disposal Method:** Incinerate in a furnace where permitted under Federal, State and local regulations. At very low concentrations in water, this product is biodegradable in biological wastewater treatment plant.

**Precautions to Be Taken in Handling and Storing:** Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in the elevated-temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions. Further information is available in a technical bulletin called "Ignition Hazards of Organic Chemical Vapors".



## **SECTION VIII - Control Measures**

Respiratory Protect (specify type): Use self-contained breathing apparatus in high vapor concentrations.

Ventilation: General (mechanical) room ventilation is expected to be satisfactory where this product is stored and handled in closed equipment. Special, local ventilation is needed at points where vapors can be expected to escape to the workplace air.

Protective Gloves: Use plastic or rubber material gloves.

Eye Protection: Monogoggles

Other Protective Clothing or Equipment: Eye wash, safety shower.

## **Notice**

KICTeam, Inc. expressly disclaims all express or implied warranties to merchantability and fitness for a particular purpose with respect to the product or information provided recognized sources. While the information is believed to be accurate, KICTeam, Inc. makes no representations as to its accuracy or sufficiency. Conditions of use are beyond KICTeam, Inc.'s control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risk of their use, handling and disposal of the product, or from the publications or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.